

TECHNICAL DATE SHEET

page 1/2

UVC single-lamp system - COMPACT T

SYSTEM TYPE			1 AF300 T	
Product			AQUAFIDES	
Manufacturer			AQUAFIDES	
DVGW type approval registry number - W294-2 (01.06.2006)			DW-9181BU0070	
OPERATING RANGE			1 AF300 T	
Flow rate certified (DVGW W294-2)	from - up to	m ³ /h	5,0 - 18,7	
Interpolation between the test points allowed			yes	
Head loss flow-max certified (without geodetical height)		bar	0,032	
Fluenz - biososimetric (W294-2)		J/m ²	400	
Type approval according DVGW W294-2 (01.06.2006)			ja	
Tr100 @ 254nm	from - up to	%	6 - 100	
Tr50 @ 254nm	from - up to	%	24,5 - 100	
Tr10 @ 254nm	from - up to	%	75,5 - 100	
SSK @ 254nm	from - up to	m-1	12,2 - 0	
Temperature of process water*	from - up to	°C	0 - 65	
CONTROL - CABINET			1 AF300 T	
Type			DigiSys Compact 300 - 400	
System design			Bus-RS485	
Control mode			digital	
Control data and software update access			USB	
Software service and settings via laptop			yes	
Control display multi 3-colours (green, yellow and red)		lines	4	
Control button for the operation of the system		button	5	
Product (control-cabinet)			Rolec	
Material (control-cabinet)			aluminium	
Colour (control-cabinet)	grey	RAL	7040	
Dimensions	width	mm	330	
	height	mm	200	
	depth	mm	120	
Weight			kg	5,2
Operating voltage (nominal voltage)		V / Hz	230 / 50	
Operating connection			1L / N / PE	
Total consumed power (normal operation)		W	270	
Power factor (normal operation)		cos φ	0,99	
Current load per phase (by nominal voltage) max.		A	1,2	
Protection class		IP	65	
Feed line fuse (data for cutout type D)		pc x A	1 x 13	
UVC lamp cable length (control-cabinet/reactor)		m	4	
Power line cable length (control-cabinet/power plug)		m	2,5	
Environmental temperature control-cabinet		°C	5 - 35	
EVG ELECTRONIC BALLAST			1 AF300 T	
Type			Compact 300 - 400	
Design		EVG	combined with controll mode	
Number of EVG's		pcs	1	
UVC lamps per EVG		pcs	1	
System design			Bus-RS485	
Control mode			digital	
UVC power line regulation		%	50 - 120	
Overall efficiency (normal operation EVG and UVC lamp)		%	≥ 90	

TECHNICAL DATE SHEET

page 2/2

UVC single-lamp system - COMPACT T

IRRADIATION CHAMBER (IC)			1 AF300 T
Irradiation chamber connection		mm	DN 65
Connecting dimensions acc. Norm (flange made of compressed plate PN)			DIN 2642
Design - lay-out inlet to outlet flange			Z - design
Irradiation chamber possible fitting positions	horizontal		yes
	vertical		yes
	reverse (UVC lamp)		yes
Material water-swept parts			stainless steel
Material number			1.4404
Material water-swept seals		O-rings	EPDM
Dimensions	width	mm	366
	height (length)	mm	1.163
	depth	mm	185
	ED Ø	mm	172
Height (length) IC including disassembling of the quartz tube		mm	2.355
Quartz tubes flanged with adapter	ED Ø	mm	38
	length	mm	1.157
Number of quartz tubes		pcs	1
Weight without medium		approx. kg	20,5
Weight with medium		approx. kg	43,9
Irradiation chamber volume		approx. l	23,4
Drain / vent (stainless steel ball valves)			G 1/4"
Irradiation chamber protection class		IP	65
Operating pressure (maximal)		bar	10
UVC LAMP			1 AF300 T
Type			AF300A
Product / Manufacturer			AQUAFIDES
Number of UVC lamps		pcs	1
UVC lamp kind			amalgam
UVC lamp power (Watt UVC per lamp - new lamp)			78,6
UVC lamp power (Watt UVC after 8.760 running hours per lamp) W (UVC)			55,0
UVC lamp power @ 253,7 nm		%	≥ 85
UVC lamp wavelength @ ≤ 240 nm			filtrated
Power consumption per UVC lamp (including EVG)		W	270
UVC lamp currentconsumption per UVC lamp (normal operation)		A	3,4
UVC lamp connection		special	4-pin
Lamp service life **		hours	12.000
UVC SENSORSYSTEM			1 AF300 T
Type			DigiNorm
Numbers of UVC sensors		pc	1
Design according ÖNORM M5873-1D			yes
Type tested according ÖNORM M5873-1D			yes
Recalibration according ÖNORM M5873-1D			yes
Calibration according ÖNORM M 5873-1D			yes
Recalibration time period		year	1
System design UVC sensor			Bus-RS485
Control mode			digital
UV measurement range		W/m ²	2 - 500
Output signal (switchable)		mA	0/4 - 20
Exactness of the measurements		%	± 2
Sensitive @ 254 nm		%	≥ 99
Temperature stability		°C	0 - 75
UVC sensor cable length		m	5

* Medium temperature: in connection with the disinfection performance – please absolutely taking into account at dimensioning the plants

** Lamp guarantee and usage agreements are mentioned in the general Terms and Conditions of UVC lamps