

TECHNICAL DATA SHEET page 1/2

UVC multiple-lamp systems 300 W - COMPACT T

SYSTEM TYPE			6 AF300 T
Product			AQUAFIDES
Manufacturer			AQUAFIDES
DVGW type approval registry number - W294-2 (01.06.2006)			DW-9181BU0281
OPERATING RANGE			6 AF300 T
Flow rate certified (DVGW W294-2)	from - up to	m ³ /h	52,0 - 205,0
Interpolation between the test points allowed			yes
Head loss flow-max certified (without geodetical height)		bar	0,055
Fluenz - biososimetric (W294-2)		J/m ²	400
Type approval according DVGW W294-2 (01.06.2006)			yes
Tr100 @ 254nm	from - up to	%	10 - 100
Tr50 @ 254nm	from - up to	%	31,6 - 100
Tr10 @ 254nm	from - up to	%	79,4 - 100
SSK @ 254nm	from - up to	m-1	10 - 0
Temperature of process water*	from - up to	°C	0 - 65
CONTROL - CABINET			6 AF300 T
Type			DigiSys with Slave Card 6 AF 300-400
System design			Bus-RS485
Control mode			digital
Control data and software update access			USB
Software service and settings via laptop			yes
Control display multi 3-colours (green, yellow and red)		lines	4
Control button for the operation of the system		button	5
Product (control-cabinet)			Rittal AE
Material (control-cabinet)			steel plate coated
Colour (control-cabinet)	grey	RAL	7035
Dimensions	width	mm	760
	height	mm	760
	depth	mm	300
Weight			kg 67
Operating voltage (nominal voltage)			V / Hz 400 / 50
Operating connection			3L / N / PE 1,650
Total consumed power (normal operation)			W 0,99
Power factor (normal operation)			cos φ 4,8 / 2,4 / 0,1
Current load per phase (by nominal voltage)	max.	A	55
Protection class			IP 3 x 16
Feed line fuse (data for cutout type D)		pc x A	8
UVC lamp cable length (control-cabinet/reactor)			m no
Power line cable length (control-cabinet/power plug)			m 5 - 35
Environmental temperature control-cabinet			°C
EVG ELECTRONIC BALLAST			6 AF300 T
Type			EVG 300 - 400 3,4 Ampere PH
Design		EVG	housing
Number of EVG's		pc	6
UVC lamps per EVG		pc	1
System design			Bus-RS485
Control mode			digital
UVC power line regulation			% 50 - 120
Overall efficiency (normal operation EVG and UVC lamp)			% ≥ 90

TECHNICAL DATA SHEET page 2/2

UVC multiple-lamp systems 300 W - COMPACT T

IRRADIATION CHAMBER			6 AF300 T
Irradiation chamber connection		mm	DN 200
Connecting dim. acc. Norm (flange made of compressed plate)			DIN 2642
Design - lay-out inlet to outlet flange			U - design
Irradiation chamber possible fitting positions	horizontal		yes
	vertical		yes
	reverse (lamp)		yes
Material water-swept parts			stainless steel
Material number			1.4404
Material water-swept seals		O-rings	EPDM
Dimensions	width	mm	500
	height (length)	mm	1.134
	depth	mm	390
	ED Ø	mm	390
Height IC including disassembling of the quartz tube		mm	2.365
Quartz tubes flanged with adapter	ED Ø	mm	38
	length	mm	1.157
Number of quartz tubes		pc	6
Weight without medium		approx. kg	116
Weight with medium		approx. kg	232
Irradiation chamber volume		approx. l	116
Drain / vent			1/2"
Irradiation chamber protection class		IP	65
Operating pressure (maximal)		bar	10
UVC LAMP			6 AF300 T
Type			AF300A
Product / Manufacturer			AQUAFIDES
Number of UVC lamps		pc	6
UVC lamp kind			amalgam
UVC lamp power (Watt UVC per lamp - new lamp)		W (UVC)	78,6
UVC lamp power (Watt UVC after 8.760 running hours per lamp)		W (UVC)	55
UVC lamp power @ 253,7 nm		%	≥ 85
UVC lamp wavelength @ ≤ 240 nm			filtered
Power consumption per UVC lamp (including EVG)		W	270
UVC lamp currentconsumption per UVC lamp (normal operation)		A	3,4
UVC lamp connection		special	4-pin
Lamp service life **		h	12.000
UVC SENSORSYSTEM			6 AF300 T
Type			DigiNorm
Numbers of UVC sensors		pc	1
Design according ÖNORM M5873-1D			yes
Type tested according ÖNORM M5873-1D			yes
Recalibration according ÖNORM M5873-1D			yes
Calibration according ÖNORM M 5873-1D			yes
Recalibration time period		year	1
System design UVC sensor			Bus-RS485
Control mode			digital
UV measurement range		W/m ²	2 - 500
Output signal (switchable)		mA	0/4 - 20
Exactness of the measurements		%	± 2
Sensitive @ 254 nm		%	≥ 99
Temperature stability		°C	0 - 75
UVC sensor cable length		m	9

* Medium temperature: in connection with the disinfection performance – please absolutely taking into account at dimensioning the plants

** Lamp guarantee and usage agreements are mentioned in the general Terms and Conditions of UVC lamps